

CMF VERTICAL BOTTOM CONNECTION



Fixed membrane expansion vessels Cooling and heating closed systems

- Fixed membrane expansion vessel for cooling and heating systems.
- Material: Steel
- Non-replaceable membrane, according to EN 13831 (non potable)
- Water connection: R 1"
- Precharge valve
- Gas precharge: Air
- External red epoxy powder coating
- Manufactured according to 2014/68/EU Directive
- 2 year warranty



Technical specifications

- | | |
|--------------------------|--------------------|
| ▪ Volume: | 500 – 1.000 Liters |
| ▪ Membrane: | Non-replaceable |
| ▪ Max. service pressure: | 6 Bar |
| ▪ Test pressure: | 9 Bar |
| ▪ Precharge EXWORKS: | 1,5Bar |
| ▪ Temperature max.: | 100°C |
| ▪ Temperature min.: | -10°C |
| ▪ Water connection: | R1" G.M |



| Weight (Kg) | Code | Model | Volume (Lts.) | Pressure (Bar) | ØD (mm) | H (mm) | Water connection R |
|-------------|----------|----------|---------------|----------------|---------|--------|--------------------|
| 63 | 04500351 | 500 CMF | 500 | 6 | 750 | 1.445 | 1" |
| 77 | 04600351 | 600 CMF | 600 | 6 | 750 | 1.700 | 1" |
| 95 | 04800351 | 800 CMF | 800 | 6 | 750 | 2.155 | 1" |
| 118 | 04101351 | 1000 CMF | 1.000 | 6 | 750 | 2.555 | 1" |